

# VSMS L5S

V-STEEL SMOOTH TREAD



CATEGORÍA	MEDIDA	RANKING	CONSTRUCCIÓN / COMPUESTO	CÓDIGO TRA	NºART	PESO	PROFUNDIDAD ESTRIA (32ND)	DIÁMETRO	ANCHO NEUMÁTICO
CHICO CON CÁMARA	9.00R20	2*	D2A	L5S	150908	240	64	41.5	10.2
	12.00R20	2*	D2A	L5S	150916	350	72	46.2	12.3
	12.00R24	2*	D2A	L5S	150924	410	72	50.2	12.3
	14.00R24	2*	D2A	L5S	211240	600	91	54.8	15.4
CHICO SIN CÁMARA	17.5R25	2*	D2A	L5S	422908	650	86	54.1	17.3
	18.00R25	1*	D2A	L5S	419397	1,110	105	65.9	20.2
	18.00R25	2*	D2A	L5S	422282	1,090	105	66.2	20.2
GIGANTE SIN CÁMARA	26.5R25	2*	D2V	L5S	422096	1,780	120	69.9	26.9
	29.5R29	2*	D2A	L5S	422134	2,450	132	79.1	30.2

Servicio de carreteras

**BRIDGESTONE**  
OFF THE ROAD TIRES

Bridgestone Americas Tire Operations, LLC

■ 535 Marriott Drive, 8th Floor Nashville, TN 37214

■ 1.800.572.8905

■ [www.bfor.com](http://www.bfor.com)